





Dimensional

Cir- cuits	Dimension mm	
	L1	L2
2x2	2.00	4.00
2x3	4.00	6.00
2x4	6.00	8.00
2x5	8.00	10.00
2x6	10.00	12.00
2x7	12.00	14.00
2x8	14.00	16.00
2x9	16.00	18.00
2x10	18.00	20.00
2x11	20.00	22.00
2x12	22.00	24.00
2x13	24.00	26.00
2x14	26.00	28.00
2x15	28.00	30.00
2x16	30.00	32.00
2x17	32.00	34.00
2x18	34.00	36.00
2x19	36.00	38.00
2x20	38.00	40.00
2x21	40.00	42.00
2x22	42.00	44.00
2x23	44.00	46.00
2x24	46.00	48.00
2x25	48.00	50.00
2x26	50.00	52.00
2x27	52.00	54.00
2x28	54.00	56.00
2x29	56.00	58.00
2x30	58.00	60.00
2x31	60.00	62.00
2x32	62.00	64.00
2x33	64.00	66.00
2x34	66.00	68.00
2x35	68.00	70.00
2x36	70.00	72.00
2x37	72.00	74.00
2x38	74.00	76.00
2x39	76.00	78.00
2x40	78.00	80.00



RoHS COMPLIANT

Recommended
P.C.Board
Hole Layout

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	DEC.06'05
B		ADD.Tin Plated	AUG.30'06
C		MODIFY P/N	MAR.02'11

SPECIFICATIONS

Current Rating:

1 Amps

Insulator resistance:
5000 Megohms Min.Dielectric withstanding:
AC 500 V

Voltage:

AC 250 V

Operating Temperature:
-40° - +105°CContact Material:
BrassInsulator Material:
Standard:P.B.T

Finish:

G=Gold flash

T=Tin Plated

TOLERANCE UNLESS OTHERWISE SPECIFIED			PROJECTION		GOLD-TEK ELECTRIC CO., LTD.	
LINEAR	ANGLE		UNITS		TITLE	PART NO.
X. ±	X' ±		MM		PITCH: 2.00x2.00mm	PHDS**G(T)22
.X ± 0.38	.X' ±				PIN HEADER	CAD NO. I642
.XX ± 0.25	.XX' ± 3°				DOUBLE ROW	SHEET
.XXX ±	.XXX' ±		SCALE		IPART NO	1 OF 1
APPD			SIZE			
CHKD						
DRAW	Z.	MAR. 02' 2011	A4			

圖面編號:GTKSD0686-C(1)