

泉州金声电子科技有限公司

Quanzhou JinSheng Electron CO., Ltd

[TEL:+86-0595-22356961-2](http://www.laba.co) [FAX:22356508](http://www.laba.co)

[Http://www.laba.co](http://www.laba.co) ADD:中国福建省泉州市浔美工业区海西电子信息产业育成基地

型号 Model	QP50CP08-66-R
尺寸 Dimension	Outer Diameter50mm Baffle Opening13.3mm Height Refer to drawing in details;
阻抗 Nominal Impedance	8 Ohm±15% At1000 HZ
额定功率 Power Rating	2.0 watt Maximum 2.5 Watt
最低共振频率 Lowest Resonant Frequency	630±20% HZ.
灵敏度 Output Sound Pressure Level (S. P. L)	93 ± 3db/1 Watt. 1Meter. Average at800, 1000, 1200, 1500HZ.
频率范围 Frequency Range	FO-5KHZ, Average SPL±10db
失真率 Distortion	3%Maximum At1000HZ 2.0 W
极性 Polarity	Diaphragm shall move forward when Apply a Postive DC current the "+" or "Marked" Terminal
寿命测试 Test	Load Bt Audio Singnal Generator At 4.0 Volts. total 48 hours and20~20KHZ Resonant Frequency

Approval Sheet for Product Specification

承认书

PRODUCT NAME	【产品名称】：	speaker
CUSTOMER PART NO	【客户型号】：	
QINGLONG PART NO	【我司型号】：	QP50CP08-56
DESCRIPTION	【规格】：	8Ω 2W
CUSTOMERS	【客户名称】：	QE-1326

【注意/note】

1. This product shall comply with RoHs. 上本品符合欧洲RoHs规定指令.
2. IN CASE OF CHANGES, SUCH AS DIE & MOLD, MANUFACTURING PROCESS, MATERIAL, APPEARANCE, AND INSPECION etc., THE SAME PROCEDURE IS REQUIRED. 此部品确认后. 如模具、制造方法、材料、外观、检查等发生变更的情况下必须事前由双方进行合议。

APPROVAL SEAL (承认印):				
DISCUSS		RESOLUTION		
QA	PURCHASE	ISSUED	CHECKED	APPROVED
		BY	BY	BY

SUPPLIER (厂名): 台湾强度电子有限公司 泉州强盛电子有限公司

TEL(电话): 86-595-22356962 **TEL(电话):** 00886-2-27491725

FAX(传真): 86-595-22356508 **FAX(传真):** 00886-2-27603649

Http://: www.speaker-iec.com

E-mail: iecspeaker@yahoo.com.cn

SIGNATURE	Issued by	Checked by	Approved by	Date
	担当	核查	确认	日期
	张桂兰	张桂兰	吴秋福	2013.05.06

异音测试 Abnormal Sound Test	Must be Normally tested Bt 4.0 Volts Sinwave
工作温度 Operation Temperature	$-20^{\circ}\text{C} \sim +50^{\circ}\text{C}$
储藏温度 Storage Temperature	$-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$

