

RML-29 Series



Special features



Adjustable Angle



High-performance COB light source




Various light colors



Excellent thermal dissipation



Different light distributions



Various sizes

Applications

- Convention Center
- Hotels
- Boutiques
- Bussiness Center
- Museums
- Home
- Offices
- Hospitals
- Leisure Space. Etc



Part number system

RML-29 - A 1 16 30 W - 15D
X1 X2 X3 X4 X5 X6 X7

X1=Series

X2=Type

X3=Number of Head

1=1 Head

2=2 Head

3=3 Head

X4=Rated power

16= 16 Watts

22= 22 Watts

30= 30 Watts

X5=Color temperature

30=3000 K

40=4000 K

57=5700 K

X7=View angle

15D= 15 °

24D= 24 °

35D= 35 °



X6=Shell color

W=White

BK=Black

RML-29 Series

Dimensions



Hole dimension

Specifications

Power factor:	≥0.5
Power-Supply Efficiency:	≥85%
Color rendering index:	RA≥80
Using Temperature:	-20°C - 50°C

Rated Power	Part No.	Luminous Flux	Color of light	Color temperature	View angle	Current	Dimensions (WxLxH)	Hole dimension	size
1x16W	RML-29-A11630W-15D	1391 Lm	Warm White	3000 K	15 °	450 mA/ 37 Vdc	122x122x85 mm.	110x110 mm.	4.5x4.5 inch
	RML-29-A11640W-15D	1461 Lm	Neutral White	4000 K					
	RML-29-A11657W-15D	1427 Lm	Daylight	5700 K					
	RML-29-A11630W-24D	1418 Lm	Warm White	3000 K	24 °				
	RML-29-A11640W-24D	1489 Lm	Neutral White	4000 K					
	RML-29-A11657W-24D	1455 Lm	Daylight	5700 K					
	RML-29-A11630W-35D	1383 Lm	Warm White	3000 K	35 °				
	RML-29-A11640W-35D	1453 Lm	Neutral White	4000 K					
	RML-29-A11657W-35D	1419 Lm	Daylight	5700 K					
1x22W	RML-29-B12230W-15D	1696 Lm	Warm White	3000 K	15 °	600 mA/ 37 Vdc	150.5x150.5x110 mm.	138x138 mm.	5x5 inch
	RML-29-B12240W-15D	1815 Lm	Neutral White	4000 K					
	RML-29-B12257W-15D	1828 Lm	Daylight	5700 K					
	RML-29-B12230W-24D	1724 Lm	Warm White	3000 K	24 °				
	RML-29-B12240W-24D	1844 Lm	Neutral White	4000 K					
	RML-29-B12257W-24D	1858 Lm	Daylight	5700 K					
	RML-29-B12230W-35D	1652 Lm	Warm White	3000 K	35 °				
	RML-29-B12240W-35D	1768 Lm	Neutral White	4000 K					
	RML-29-B12257W-35D	1781 Lm	Daylight	5700 K					
1x30W	RML-29-C13030W-15D	2282 Lm	Warm White	3000 K	15 °	800 mA/ 37 Vdc	174x174x130 mm.	160x160 mm.	6x6 inch
	RML-29-C13040W-15D	2355 Lm	Neutral White	4000 K					
	RML-29-C13057W-15D	2357 Lm	Daylight	5700 K					
	RML-29-C13030W-24D	2172 Lm	Warm White	3000 K	24 °				
	RML-29-C13040W-24D	2241 Lm	Neutral White	4000 K					
	RML-29-C13057W-24D	2244 Lm	Daylight	5700 K					
	RML-29-C13030W-35D	2170 Lm	Warm White	3000 K	35 °				
	RML-29-C13040W-35D	2240 Lm	Neutral White	4000 K					
	RML-29-C13057W-35D	2242 Lm	Daylight	5700 K					