

ZW-12026-6



Devices Support

Card reader:

- Four slot reader supports the following formats:
- Smart Card slot supports ATM / CAC / ID / IC / SIS cards,
- microSD slot supports microSD / microSDHC / microSDXC / TransFlash cards,
- SD slot supports SecureDigital, SDHC, SDXC, MultiMedia Card, MMC 4.0, MMC Dual Voltage, MMC mobile, RS-MMC cards, miniSD, miniSDHC, MMC Micro cards with adapter,
- SIM slot supports standard size SIM cards (microSIM and nanoSIM with adapter).

Smart Cards specification support:

- Supports ISO 7816 Class A, B and C smart cards (5V, 3V and 1.8V).
- Supports ISO 7816, EMV 4.1 (EMV 2000 level 1) standards.
- Supports protocols T 0 and T=1, I2C, SLE 4432/42 (S=10), SLE 4418/28 (S=9).
- PC/SC 2.0 PC Smart Card support.
- Microsoft Smart Card for Windows support.
- Supports I2C cards SLE4418, SLE4428, SLE4432, SLE4442, SLE4436, SLE5536, SLE6636, AT88SC1608, AT45D041.
- Microsoft WHQL USB Smart Card Reader compliant.
- FIPS 201 standard compliant.
- 420 Kbps Smart Card interface speed (depends on card).

Memory Cards specification support:

- SD 1.0/1.1 (SD - Secure Digital, up to 2GB) compliant.
- SD 2.0 (SDHC - Secure Digital High Capacity, up to 32GB) compliant.
- SD 3.0 (SDXC - Secure Digital eXtended Capacity, up to 2TB) compliant.
- MMC and eMMC 3.x/4.0/4.1/4.2.

Supported operating systems:

- Windows 10/11 and later, Mac OS 10.15 and later.

Product details

Interface	USB 2.0 / USB 1.1
Rate	480 / 12 Mbit/s (high / full speed)
Connector	USB Type A male (on the cable)
Cable	1.6 m, permanently connected
Number of slots	4
SD slot	SD / SDHC / SDXC, MMC, MMC mobile, RS-MMC, with miniSD / miniSDHC / MMC Micro adapter
MicroSD slot	microSD / microSDHC / microSDXC / TransFlash
Slot SIM	SIM cards standard size
Slot Smart Card	ATM / CAC / ID / IC / SIS
Automatic installation	YES
Plug and Play	YES
Product weight	91g
Size	77 x 54 x 52mm
Color	Black